

Single-thread, Chainstitch Basting Machine



- High efficient basting works at a sewing speed of 1,800rpm.
- Chainstitch is continuously formed with a single thread and by a blind looper which eliminates the need for a bobbin thread refilling. In addition, the basted seam can be easily undone.
- Basting works are efficiently done with a maximum stitch length of 10mm which is easily set up by a control dial.

SPECIFICATIONS

Model name	ML-111
Max. sewing speed	1,800rpm
Max. stitch length	10mm
Needle bar stroke	35mm
Lift of the presser foot	By hand: 5.5mm, By knee: 12mm
Needle (at the time of delivery)	TV × 7 (#14) #11 ~ #14
Thread take-up	Needle bar thread take up
Feed dog	3-row feed dog
Looper	Blind looper
Lubrication	By an oiler
Lubricating oil	JUKI New Defrix Oil No.1 (equivalent to ISO VG7)
Distance from needle to machine arm	300mm
Size of bed	476mm × 178mm
Weight of the machine	29kg

APPLICATIONS

- The basting of the front edges, edge and stand of collars, flaps of men's and ladies' suits and coats.
- The basting of the waist bands, the flies of trousers slacks, etc.







JUKI CORPORATION HEAD OFFICE



8-2-1, KOKURYO-CHO, CHOFU-SHI, TOKYO 182-8655, JAPAN PHONE : (81) 3-3430-4001 ~ 4 FAX : (81) 3-3430-4909.4914 TELEX: J22967

http://www.juki.com

* Specifications and appearance are subject to change without prior notice for improvement.

* Read the instruction manual before putting the machine into service to ensure safety.

* This catalog is printed on recycle paper.